

LINEA 22 T




LINEA 22 T

Linea led luminosa per applicazioni interne. Corpo in alluminio nelle finiture anodizzato naturale, verniciato bianco e nero. Diffusori in policarbonato opalino. Completa di terminali di chiusura in plastica, di accessori di fissaggio e 2 metri di cavo di alimentazione. Personalizzabile con taglio su misura fino a 6 metri. Misura diametro 22 mm. Garanzia di 5 anni.

| | |
|--------------------------|-------------------------------|
| installazione | sospensione |
| utilizzo | interno |
| alimentazione | 24V DC (*) |
| potenza per metro | 12W/m 18W/m 24W/m RGB |
| sorgente luminosa | led |
| temperatura colore | 2700K 3000K 4000K |
| indice di resa cromatica | CRI > 90 |
| diffusore standard | opalino diffondente beam 120° |
| dimmerazione | On/Off, dimmerabile |
| classe di isolamento | III |

(*) Alimentatore remoto non incluso
(*) Remote Driver not included

120°



IT 04/2024 ailis srl Contenuti tecnici aggiornati.
Con riserva di modifiche.



Installazione a sospensione
Pending installation

SEZIONE / SECTION



22mm

FINITURA / FINISH

WT Bianco
White

BK Nero
Black

AL Anodizzato naturale
Natural anodized

DIFFUSORI / DIFFUSERS

DIFF-0100-OP
Policarbonato opalino

LINEA 22 T cablata con certificazione CE

| ITEM | WATT | LUMEN | BEAM ANGLE | DRIVER | PROTECTION LEVEL | FINISH |
|------------------------------|-------|-------|------------|--------|------------------|-------------------------|
| LIN-22T-_-IP30-12-2700K-_-_- | 12W/m | 1200 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-18-2700K-_-_- | 18W/m | 1800 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-24-2700K-_-_- | 24W/m | 2400 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-12-3000K-_-_- | 12W/m | 1200 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-18-3000K-_-_- | 18W/m | 1800 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-24-3000K-_-_- | 24W/m | 2400 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-12-4000K-_-_- | 12W/m | 1220 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-18-4000K-_-_- | 18W/m | 1840 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-24-4000K-_-_- | 24W/m | 2450 | 120° | Remote | IP 30 | White, Black, Aluminium |
| LIN-22T-_-IP30-18-RGB-NQ-_- | 18W/m | | | Remote | IP 30 | White, Black, Aluminium |

CODICE D'ORDINE / ORDER CODE

LIN-22-T-_-IP30-18-2700K-_-_-

WT BK AL

lunghezza in cm / length in centimeters

ESEMPIO / EXAMPLE

LIN-22-T-WT-IP30-18-4000K-250